

STANDARD

CO2 EMISSIONS

CONSUMPTION

Diavel V4 ENGINE TYPE V4 Granturismo, V4 - 90°, 4 valves per cylinder, counter-rotating crankshaft, Twin Pulse firing order, liquid cooled DISPLACEMENT 1,158 cc (71 cu in) BORE X STROKE 13 mm x 53.5 mm COMPRESSION RATIO 4.0:1 POWER 68 hp (124 kW) @ 10.750 rpm TORQUE 12.8 kgm (126 Nm, 93 lb ft) @ 7,500 rpm FUEL INJECTION Electronic fuel injection system, Øeq 46 mm elliptical throttle bodies with Ride-by-Wire system stainless steel exhaust muffler with 4 exit pipes, 2 catalytic converters and 4 lambda probes EXHAUST TRANSMISSION GEARBOX speed with Ducati Quick Shift PRIMARY DRIVE traight cut gears; Ratio 1.80:1 RATIO 1=40/13, 2=36/16, 3=34/19, 4=31/21, 5=29/23, 6=27/25 FINAL DRIVE hain, front sprocket z16, rear sprocket z43 CLUTCH vdraulically controlled slipper and self-servo wet multiplate clutch CHASSIS FRAME Aluminum monocoque frame FRONT SUSPENSION Ø 50 mm fully adjustable usd fork FRONT WHEEL ight allov cast. 3.5" x 17" FRONT TYRE irelli Diablo Rosso III, 120/70 ZR17 REAR SUSPENSION Fully adjustable monoshock, aluminium single-sided swingarm REAR WHEEL Light alloy cast, 8,0" x 17" REAR TYRE Pirelli Diablo Rosso III, 240/45 ZR17 WHEEL TRAVEL (FRONT/REAR) 20 mm / 145 mm (4.7 in / 5.7 in) 2 x Ø 330 mm semi-floating discs, radially mounted Brembo Stylema monobloc 4-piston callipers, radial master cylinder PR16/19, FRONT BRAKE ornering ABS ع 265 mm disc, Brembo 2-piston floating calliper, Cornering ABS REAR BRAKE INSTRUMENTATION DIMENSIONS AND WEIGHTS " TFT colour display DRY WEIGHT 211 kg (465 lb) KERB WEIGHT 36 kg (520 lb) SEAT HEIGHT 790 mm (31 1 in) WHEELBASE ,593 mm (62.7 in) RAKE 6° TRAIL 12 mm (4.4 in) FUEL TANK CAPACITY 20 l (5.3 US gal) NUMBER OF SEATS EOUIPMENT Riding Modes, Power Modes, Cornering ABS, Ducati Traction Control, Ducati Wheelie Control, Davtime Running Light\*, Ducati SAFETY EQUIPMENT Brake Light Ducati Quick Shift, Ducati Power Launch, Cruise control, Hands-Free, 5" TFT colour display, Ducati Multimedia System, Backlit handlebar switches, Full-LED lighting system, Dynamic turn indicators\* STANDARD EQUIPMENT PROVIDED FOUIPMENT READY FOR WARRANTY AND MAINTENANCE ırn-by-Turn navigation syster WARRANTY 24 months, unlimited mileage MAINTENANCE SERVICE INTERVALS 15,000 km (9,000 miles) / 24 months VALVE CLEARANCE ADJUSTMENT KM 50,000 km (36,000 miles) ITRIES WHERE EURO 5 STANDARD APPLIES) EMISSIONS AND CONSUPTION (ONLY FOR COU

\*Please check with your dealer product availability. Bike specifications and equipment may vary from market to market. Please refer to your local dealer for further information

Euro 5

54 g/k

5.4.1/100.km